SAFETY DATA SHEET



Brake Cleaner

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name	:	Brake Cleaner
Product code	:	hansa
Color	:	Colorless.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Aerosol product-Cleaning agent-Preparation of material for applicat	วท
-	

1.3 Details of the supplier of the safety data sheet

HANSA-FLEX AG Zum Panrepel 44, D-28307 Bremen Phone 0421/48907-0, Fax 0421/48907-88 E-Mail info@hansa-flex.com Internet www.hansa-flex.com

e-mail address of person : info@hansa-flex.com responsible for this SDS

1.4 Emergency telephone number

Telephone number

: Giftinformationszentrum Nord GIZ-Nord +49(0)551-19 240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aerosol 1, H222, H229 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Hazard pictograms



Signal word	: Danger
Hazard statements	 H222, H229 - Extremely flammable aerosol. Pressurized container: may burst if heated. H315 - Causes skin irritation. H336 - May cause drowsiness or dizziness. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements	

SECTION 2: Hazards identification

Prevention	:	 P280 - Wear protective gloves. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P261 - Avoid breathing dust or mist. P264 - Wash thoroughly after handling. P251 - Do not pierce or burn, even after use.
Response	:	P391 - Collect spillage. P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell. P362 + P364 - Take off contaminated clothing and wash it before reuse.
Storage	:	P405 - Store locked up. P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
Disposal	:	P501 - Dispose of waste according to applicable legislation.
Hazardous ingredients	:	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
Supplemental label elements	:	Contains (R)-p-mentha-1,8-diene. May produce an allergic reaction.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	Aspiration hazard - Not applicable.

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	REACH #: 01-2119475514-35 EC: 921-024-6 CAS: -	≥50 - ≤75	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411	[1]
pentane	REACH #: 01-2119459286-30 EC: 203-692-4 CAS: 109-66-0 Index: 601-006-00-1	≥10 - <20	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 EUH066	[1] [2]
ethanol	REACH #: 01-2119457610-43 EC: 200-578-6 CAS: 64-17-5 Index: 603-002-00-5	≤10	Flam. Liq. 2, H225	[2]

SECTION 3: Compos	sition/information on i	ngredients		
butane	REACH #: 01-2119474691-32 EC: 203-448-7 CAS: 106-97-8 Index: 601-004-00-0	≤10	Flam. Gas 1A, H220 Press. Gas (Comp.), H280	[2]
propan-2-ol	REACH #: 01-2119457558-25 EC: 200-661-7 CAS: 67-63-0 Index: 603-117-00-0	≤3	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1] [2]
(R)-p-mentha-1,8-diene	REACH #: 01-2119529223-47 EC: 227-813-5 CAS: 5989-27-5 Index: 601-029-00-7	≤0.3	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such
Deta of issue (Deta of musician	DE 00 0004 Dete of maximum incurs in the maximum reliability Maximum of 2/40

SECTION 4: First aid	measures
	as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
4.2 Most important symptom Over-exposure signs/symp	ns and effects, both acute and delayed toms
Eye contact	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
4.3 Indication of any immedi	ate medical attention and special treatment needed
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
SECTION 5: Firefigh	ting measures
5.1 Extinguishing media Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising f	rom the substance or mixture
Hazards from the substance or mixture	: Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Date of issue/Date of revision	: 25.02.2021 Date of previous issue : No previous validation Version : 1 4/16

SECTION 5: Firefighting measures

equipment for fire-fighters br m cc	ire-fighters should wear appropriate protective equipment and self-contained reathing apparatus (SCBA) with a full face-piece operated in positive pressure node. Clothing for fire-fighters (including helmets, protective boots and gloves) proforming to European standard EN 469 will provide a basic level of protection for nemical incidents.
---	--

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
6.3 Methods and materials for containment and cleaning up	:	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapor or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

5/16

SECTION 7: Handling and storage

Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold	
P3a	150 tonne	500 tonne	
E2	200 tonne	500 tonne	

7.3 Specific end use(s)

Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

pentane ethanol butane propan-2-ol	 EH40/2005 WELs (United Kingdom (UK), 8/2018). TWA: 600 ppm 8 hours. TWA: 1800 mg/m³ 8 hours. EH40/2005 WELs (United Kingdom (UK), 8/2018). TWA: 1000 ppm 8 hours. TWA: 1920 mg/m³ 8 hours. EH40/2005 WELs (United Kingdom (UK), 8/2018). STEL: 1810 mg/m³ 15 minutes. STEL: 750 ppm 15 minutes. TWA: 1450 mg/m³ 8 hours. TWA: 600 ppm 8 hours. EH40/2005 WELs (United Kingdom (UK), 8/2018).
butane	TWA: 1800 mg/m ³ 8 hours. EH40/2005 WELs (United Kingdom (UK), 8/2018). TWA: 1000 ppm 8 hours. TWA: 1920 mg/m ³ 8 hours. EH40/2005 WELs (United Kingdom (UK), 8/2018). STEL: 1810 mg/m ³ 15 minutes. STEL: 750 ppm 15 minutes. TWA: 1450 mg/m ³ 8 hours. TWA: 600 ppm 8 hours.
butane	 EH40/2005 WELs (United Kingdom (UK), 8/2018). TWA: 1000 ppm 8 hours. TWA: 1920 mg/m³ 8 hours. EH40/2005 WELs (United Kingdom (UK), 8/2018). STEL: 1810 mg/m³ 15 minutes. STEL: 750 ppm 15 minutes. TWA: 1450 mg/m³ 8 hours. TWA: 600 ppm 8 hours.
butane	TWA: 1000 ppm 8 hours. TWA: 1920 mg/m ³ 8 hours. EH40/2005 WELs (United Kingdom (UK), 8/2018). STEL: 1810 mg/m ³ 15 minutes. STEL: 750 ppm 15 minutes. TWA: 1450 mg/m ³ 8 hours. TWA: 600 ppm 8 hours.
	TWA: 1920 mg/m ³ 8 hours. EH40/2005 WELs (United Kingdom (UK), 8/2018). STEL: 1810 mg/m ³ 15 minutes. STEL: 750 ppm 15 minutes. TWA: 1450 mg/m ³ 8 hours. TWA: 600 ppm 8 hours.
	EH40/2005 WELs (United Kingdom (UK), 8/2018). STEL: 1810 mg/m ³ 15 minutes. STEL: 750 ppm 15 minutes. TWA: 1450 mg/m ³ 8 hours. TWA: 600 ppm 8 hours.
	STEL: 1810 mg/m ³ 15 minutes. STEL: 750 ppm 15 minutes. TWA: 1450 mg/m ³ 8 hours. TWA: 600 ppm 8 hours.
propan-2-ol	STEL: 750 ppm 15 minutes. TWA: 1450 mg/m ³ 8 hours. TWA: 600 ppm 8 hours.
propan-2-ol	TWA: 1450 mg/m ³ 8 hours. TWA: 600 ppm 8 hours.
propan-2-ol	TWA: 600 ppm 8 hours.
propan-2-ol	
propan-2-ol	EH40/2005 WELs (United Kingdom (UK), 8/2018).
	(e,, e).
	STEL: 1250 mg/m ³ 15 minutes.
	STEL: 500 ppm 15 minutes.
	TWA: 999 mg/m ³ 8 hours.
	TWA: 400 ppm 8 hours.
procedures atmosphere of the ventil protective e the following the assess limit values atmosphere of exposure (Workplace for the mea	Let contains ingredients with exposure limits, personal, workplace e or biological monitoring may be required to determine the effectiveness lation or other control measures and/or the necessity to use respiratory equipment. Reference should be made to monitoring standards, such as g: European Standard EN 689 (Workplace atmospheres - Guidance for ment of exposure by inhalation to chemical agents for comparison with and measurement strategy) European Standard EN 14042 (Workplace es - Guide for the application and use of procedures for the assessment e to chemical and biological agents) European Standard EN 482 e atmospheres - General requirements for the performance of procedures asurement of chemical agents) Reference to national guidance for methods for the determination of hazardous substances will also be
DNELs/DMELs	

Product/ingredient name	Туре	Exposure	Value	Population	Effects
pentane	DNEL	Long term Oral	214 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	214 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	432 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	643 mg/m³	General population	Systemic
	DNEL	Long term Inhalation	3000 mg/ m³	Workers	Systemic
propan-2-ol	DNEL	Long term Oral	26 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	89 mg/m³	General population	Systemic
	DNEL	Long term Dermal	319 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	500 mg/m³	Workers	Systemic
	DNEL	Long term Dermal	888 mg/kg bw/day	Workers	Systemic
(R)-p-mentha-1,8-diene	DNEL	Long term Oral	4.76 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	8.33 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	33.3 mg/m³	Workers	Systemic
	DNEL	Short term Dermal	0.111 mg/ cm²	General population	Local
	DNEL	Short term Dermal	0.222 mg/ cm²	Workers	Local

PNECs

No PNECs available.

8.2 Exposure controls	
Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
Individual protection meas	<u>ures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Date of issue/Date of revision

7/16

SECTION 8: Exposure controls/personal protection

	• •
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Recommended : 1 - 4 hours (breakthrough time): nitrile rubber 4 - 8 hours (breakthrough time): Viton®/butyl rubber
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended : organic vapor (Type AX) and particulate filter
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

<u>Appearance</u>	
Physical state	: Aerosol.
Color	: Colorless.
Odor	: Characteristic.
Odor threshold	: Not available.
Melting point/freezing point	: Not available.
Initial boiling point and boiling range	: Not available.
Flammability (solid, gas)	: Not available.
Upper/lower flammability or explosive limits	: Lower: 0.8% Upper: 15%
Flash point	: Closed cup: Not applicable.
Auto-ignition temperature	: Not applicable.
Decomposition temperature	: Not available.
рН	: Not applicable.
Viscosity	: Not available.
Solubility(ies)	: Not available.
Solubility in water	: 5 g/l
Partition coefficient: n-octanol/ water	: Not applicable.

Date of issue/Date of revision

SECTION 9: Physical and chemical properties

Vapor pressure	: 57.3 kPa (429.79 mm Hg) [room temperature]
Evaporation rate	: Not available.
Relative density	: Not available.
Density	: 0.669 g/cm³ [20°C (68°F)]
Vapor density	: Not available.
Explosive properties	: Not available.
Oxidizing properties	: Not available.
Particle characteristics	
Median particle size	: Not applicable.
SADT	: Not available.
SAPT	: Not available.
Heat of combustion	: 13.82 kJ/g
Aerosol product	
Type of aerosol	: Spray

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: Avoid all possible sources of ignition (spark or flame).
10.5 Incompatible materials	: No specific data.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
pentane	LC50 Inhalation Vapor	Rat	364 g/m³	4 hours
propan-2-ol	LD50 Dermal	Rabbit	12800 mg/kg	-
	LD50 Oral	Rat	5000 mg/kg	-
(R)-p-mentha-1,8-diene	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	4400 mg/kg	-
Conclusion/Summary	: Not available.			

Acute toxicity estimates

	ATE value
Not available.	

Irritation/Corrosion

SECTION 11: Toxicol				T	1
Product/ingredient name	Result	Species	Score	Exposure	Observation
propan-2-ol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 mg	-
	Eyes - Moderate irritant	Rabbit	-	10 mg	-
	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
(R)-p-mentha-1,8-diene	Skin - Mild irritant	Rabbit	-	24 hours 10 %	-
Conclusion/Summary	: Not available.	·	•		
<u>Sensitization</u>					
Conclusion/Summary	: Not available.				
<u>Mutagenicity</u>					
Conclusion/Summary	: Not available.				
<u>Carcinogenicity</u>					
Conclusion/Summary	: Not available.				
Reproductive toxicity					
Conclusion/Summary	: Not available.				
<u>Teratogenicity</u>					
Conclusion/Summary	: Not available.				

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Category 3	-	Narcotic effects
pentane	Category 3	-	Narcotic effects
propan-2-ol	Category 3	-	Narcotic effects

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Product/ingredient name	Result
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n- hexane	ASPIRATION HAZARD - Category 1
pentane	ASPIRATION HAZARD - Category 1

Information on the likely : Not available. routes of exposure

Potential acute health effects		
Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact	:	Causes skin irritation.
Ingestion	:	Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Date of issue/Date of revision

SECTION 11: Toxicological information

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	ects
Not available.	
Conclusion/Summary	: Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Other information

: Not available.

SECTION 12: Ecological information

12.1 Toxicity

ute EC50 7550 mg/l Fresh water		+
	Daphnia - Daphnia magna - Neonate	48 hours
ute LC50 1400000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
ute LC50 4200 mg/l Fresh water	Fish - Rasbora heteromorpha	96 hours
ute EC50 421 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
ute EC50 688 µg/l Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
u	te LC50 4200 mg/l Fresh water te EC50 421 μg/l Fresh water	te LC50 1400000 μg/l Marine water te LC50 4200 mg/l Fresh water te EC50 421 μg/l Fresh water te EC50 688 μg/l Fresh water te EC50 688 μg/l Fresh water

SECTION 12: Ecological information

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
pentane	3.45	171	low
propan-2-ol	0.05	-	low
(R)-p-mentha-1,8-diene	4.38	-	high

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods

Product

Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
II	

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue (EWC)

Waste code	Waste designation
16 05 04*	gases in pressure containers (including halons) containing hazardous substances
Packaging Methods of disposal	 The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not factible.
	when recycling is not feasible.
Type of packaging	European waste catalogue (EWC)
15 01 04 15 01 02	metallic packaging plastic packaging
Special precautions	: This material and its container must be disposed of in a safe way. Empty containers

This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

SECTION 14: Transport information

SECTION 14:	ranspo	ort information		
		ADR/RID	IMDG	IATA
14.1 UN number	UN1950		UN1950	UN1950
14.2 UN proper shipping name	AEROSO	LS	AEROSOLS	Aerosols, flammable
14.3 Transport hazard class(es)	2	¥2	2.1	2.1
14.4 Packing group	-		-	-
14.5 Environmental hazards	Yes.		Yes. Hydrocarbons, C6-C7, n- alkanes, isoalkanes, cyclics, <5% n-hexane, pentane	Yes. The environmentally hazardous substance mark is not required.
Additional informat	tion			-
ADR/RID		sizes of ≤5 L or ≤5 <u>Limited quantity</u> 1	kg.	not required when transported in
IMDG		Emergency sched		nsported in sizes of ≤5 L or ≤5 kg. 59
ΙΑΤΑ		: The environmentall transportation regu <u>Quantity limitation</u> 203. Cargo Aircraf Passenger Aircraft:	ly hazardous substance mark ma lations. <u>1</u> Passenger and Cargo Aircraft:	ay appear if required by other 75 kg. Packaging instructions: ctions: 203. Limited Quantities -
14.6 Special precau user	tions for			ort in closed containers that are ng the product know what to do in

14.7 Transport in bulk : Not available. according to IMO instruments

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

SECTION 15: Regulatory information

Annex XVII - Restrictions : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Restrictions on Manufacture, Marketing and Use

Product name	CAS #	%	Restriction
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	-	50 - 75	3
pentane	109-66-0	10 - 25	3
butane	106-97-8	3 - 10	28, 29
ther EU regulations			
ndustrial emissions : Not listed			
integrated pollution			
prevention and control) -			
Air			
ndustrial emissions : Not listed			
(integrated pollution prevention and control) -			
Water			
Dzone depleting substances (1005/2009/EU)			
Not listed.			
Not listed.			
Prior Informed Consent (PIC) (649/2012/EU)			
Not listed.			
Persistent Organic Pollutants			
Not listed.			
Aerosol dispensers :			
2			
3			
•			

Extremely flammable

Detergents - Regulation (EC) No 907/2006 Annex VIIA - Labelling for Contents

Identification	Concentration	
aliphatic hydrocarbons (R)-p-mentha-1,8-diene	30% and more less than 5%	

VOC content VOC (g/L) : 99,98% : 668,9

Seveso Directive

This product is controlled under the Seveso Directive.

Danger criteria

Category	
P3a E2	
E2	

SECTION 15: Regulatory information

National regulations

Product/ingredient name	List name	Name on list	Classification	Notes
butane	UK Occupational Exposure Limits EH40 - WEL	butane	Carc.	-

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list

Australia	: All components are listed or exempted.
Canada	: All components are listed or exempted.
China	: All components are listed or exempted.
Europe	: All components are listed or exempted.
Japan	: All components are listed or exempted.
New Zealand	: Not determined.
Philippines	: Not determined.
Republic of Korea	: Not determined.
Taiwan	: Not determined.
Turkey	: All components are listed or exempted.
United States	: Not determined.
Viet Nam	: Not determined.

15.2 Chemical Safety: This product contains substances for which Chemical Safety Assessments are still
required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and	: ATE = Acute Toxicity Estimate
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.
2	1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

SECTION 16: Othe	r information		
Classification			Justification
Aerosol 1, H222, H229 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411			On basis of test data Calculation method Calculation method Calculation method
Full text of abbreviated H	<u>statements</u>		
H220 H222, H229 H225		Extremely flammable Extremely flammable heated. Highly flammable liq	e aerosol. Pressurized container: may burst if
H226 H280 H304 H315		Flammable liquid an Contains gas under	d vapor. pressure; may explode if heated. owed and enters airways.
H317 H319 H336 H400		May cause an allerg Causes serious eye May cause drowsine Very toxic to aquatic	ic skin reaction. irritation. ss or dizziness.
H400 H410 H411 EUH066		Very toxic to aquatic Toxic to aquatic life	life with long lasting effects. with long lasting effects. may cause skin dryness or cracking.
Full text of classifications	[CLP/GHS]		
Aerosol 1 Aquatic Acute 1 Aquatic Chronic 1 Aquatic Chronic 2 Asp. Tox. 1 Eye Irrit. 2 Flam. Gas 1A Flam. Liq. 2 Flam. Liq. 3 Press. Gas (Comp.) Skin Irrit. 2 Skin Sens. 1 STOT SE 3		AQUATIC HAZARD AQUATIC HAZARD ASPIRATION HAZA SERIOUS EYE DAM FLAMMABLE GASE FLAMMABLE LIQUI FLAMMABLE LIQUI GASES UNDER PR SKIN CORROSION/ SKIN SENSITIZATIO	(ACUTE) - Category 1 (LONG-TERM) - Category 1 (LONG-TERM) - Category 2 RD - Category 1 IAGE/ EYE IRRITATION - Category 2 S - Category 1A DS - Category 2 DS - Category 3 ESSURE - Compressed gas IRRITATION - Category 2
Date of printing	: 25.02.2021		
Date of issue/ Date of revision	: 25.02.2021		
Date of previous issue	: No previous va	alidation	
Version	: 1		

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.